



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Spackling Paste

PRODUCT DESCRIPTION

DAP Spackling Paste is a ready mixed, easy-to-use patching compound used to fill holes and cracks and prep surfaces prior to painting. The product has a smooth working consistency and sands easily. Recommended for interior use only.



PACKAGING	COLOR	UPC
½ Pint	White	7079810200
Quart	White	7079810204

KEY FEATURES & BENEFITS

- Ready to use
- Sandable
- Interior use only

SUGGESTED USES

Ideal for filling and concealing small holes, cracks, dents and defects on:

- Plaster
- Wallboard
- Wood

FOR BEST RESULTS

- Do not use as a skim coat
- Close tightly after each use.
- Store in a cool, dry place away from extreme heat or cold.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION

1. Surface must be clean, dry and free of all foreign material. Use sandpaper to dull glossy surfaces before repairing.
2. Stir thoroughly before use. Apply with a clean putty knife.
3. For a smoother finish, dip putty knife in water and lightly smooth spackling.
4. For repairs deeper than ¼", apply two or more thin layers allowing to dry between applications.
5. Spackling Paste can be sanded or painted in 3 to 6 hours, depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid the generation of dust.
6. Clean tools immediately with water. Dried material must be cut, scraped or sanded away.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Paste
Vehicle	VAE Copolymer
Volatile	Water
Filler	Inert Filler
Odor	Slight Acetate
Weight/Gallon	14.8 +/- .2 pounds
Solids	70.8 +/- 1% by weight
Application Temperature	50°F or higher
Service Temperature	0°F to 150°F
Shelf Life	12 months
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	3 to 6 hours depending on temperature, relative humidity and depth of fill
Painting	Yes, takes either oil or latex-based paints



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

CLEAN UP & STORAGE

Wash tools immediately after use with water. Dried material must be sanded or scraped away. Close container tightly. Store in a cool, dry place.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform as directed, within one year from the date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com