



## Dynasolve ISO-Neutralizer

Liquid Isocyanate Cleaning Solvent



Dynasolve ISO-Neutralizer is a companion product to Dynaloy's urethane cleaning solvents. It is used to remove any excess liquid isocyanate from urethane-processing equipment prior to cleaning the system with Dynasolve CU-6.

### APPLICATIONS:

Flushing liquid isocyanate from urethane processing equipment

### ADVANTAGES:

More efficient than acetone, MEK and other solvents

High flash point

### SPECIFICATIONS:

Specific gravity: 0.96

Boiling point: > 464°F (> 240C)

Flash point: 230°F (110°C)

### MATERIALS REMOVED:

Liquid isocyanate

### PRODUCT USAGE GUIDELINES

(SEE SDS FOR EH&S INFORMATION)

1. Pour room-temperature Dynasolve ISO-neutralizer into isocyanate feed tank and circulate to mix with free isocyanate remaining in the system.
2. Heat to 150°F (65°C) for faster results.
3. After 10-15 minutes of mixing, drain the mixture.
4. Now that the liquid isocyanate is removed from the system, the Dynasolve-CU6 product can be used to flush uncured material and remove crystallized isocyanate.

### MATERIAL COMPATIBILITY:

**Recommended materials including:**

All metals

Teflon®

Polyethylene & polypropylene

**Avoid materials including:**

Viton®

PVC

Neoprene



VERSUM MATERIALS, LLC

The information contained herein is offered without charge for use by technically qualified personnel at their discretion and risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and no warranty of any kind is made with respect thereto.

*Versum and the Versum Materials logo are trademarks of Versum Materials, Inc. © 2017 Versum Materials, Inc.*

325-17-079-GLOBAL



1-800-375-0605  
Option 8 for 24/7 Service



6550 Oley Speaks Way  
Canal Winchester, OH 43110



[www.RudolphBros.Com](http://www.RudolphBros.Com)  
[RBCsupport@RudBro.Com](mailto:RBCsupport@RudBro.Com)