









Version 1.0 Revision Date 02/20/2019 SDS Number 300000078629 Print Date 05/08/2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Dynasolve M-35

Product Use Description : Epoxy flushing solvent

Manufacturer/Importer/Distribu

tor

 Versum Materials US, LLC 8555 South River Parkway Tempe, AZ 85284-2601 Exporter EIN No. 47-5632014 www.versummaterials.com

Telephone : 800 837 2724

Emergency telephone number

: 1-800-424-9300

(24h)

(+1) 703-741-5970 (CHEMTREC)

2. HAZARDS IDENTIFICATION

GHS classification

Serious Eye Damage/Eye Irritation - Category 2A

GHS label elements

Hazard pictograms/symbols



Signal Word: Warning

Hazard Statements:

H319: Causes serious eye irritation.

Precautionary Statements:

Prevention : P264:Wash thoroughly after handling.

P280:Wear protective gloves/protective clothing/eye protection/face protection.

Version 1.0 Revision Date 02/20/2019 SDS Number 300000078629 Print Date 05/08/2019

Response : P305+P351+P338 :IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 :If eye irritation persists: Get medical advice/attention.

Hazards not otherwise classified

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Concentration (Weight)
Ethylene di(acetate)	111-55-7	40% - 60 %
Propylene carbonate	108-32-7	40% - 60 %

4. FIRST AID MEASURES

General advice : Seek medical advice. If breathing has stopped or is labored, give assisted

respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.

Eye contact : Rinse immediately with plenty of water also under the eyelids for at least 20

minutes. Remove contact lenses.

Skin contact : Wash off immediately with plenty of water for at least 20 minutes.

Ingestion : Never give anything by mouth to an unconscious person. Prevent aspiration of

vomit. Turn victim's head to the side.

Inhalation : Treat symptomatically. Move to fresh air.

Most important

symptoms/effects - acute and

delayed

Repeated and/or prolonged exposures may result in : Adverse skin effects

(such as defatting, rash or irritation) Eye disease.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam.

Carbon dioxide (CO2).

Dry chemical. Dry sand.

Limestone powder.

Specific hazards : Incomplete combustion may form carbon monoxide. Burning produces noxious

and toxic fumes. Downwind personnel must be evacuated.

2/9

Versum Materials US,LLC

Version 1.0 Revision Date 02/20/2019 SDS Number 300000078629 Print Date 05/08/2019

Special protective equipment

for fire-fighters

: Use personal protective equipment. Wear self contained breathing apparatus

for fire fighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures : Wear suitable protective clothing, gloves and eye/face protection. Evacuate

personnel to safe areas.

Environmental precautions : Construct a dike to prevent spreading.

Methods for cleaning up : Approach suspected leak areas with caution. Call Emergency Response

number for advice. Place in appropriate chemical waste container.

Additional advice : If possible, stop flow of product.

7. HANDLING AND STORAGE

Handling

Avoid contact with eyes. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures

Provide readily accessible eye wash stations and safety showers.

Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits.

Personal protective equipment

Respiratory protection : Wear appropriate respirator when ventilation is inadequate.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard

should be worn at all times when handling chemical products if a risk

assessment indicates this is necessary.

Eye protection : Full face shield with goggles underneath.

Skin and body protection : Long sleeve shirts and trousers without cuffs.

Special instructions for : Wash hands at the end of each workshift and before eating, smoking or using

3/9

Versum Materials US,LLC

Version 1.0 Revision Date 02/20/2019 SDS Number 300000078629 Print Date 05/08/2019

protection and hygiene

the toilet. Provide readily accessible eye wash stations and safety showers.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid. Colorless - Light yellow

Odor : No data available.

Odor threshold : No data available.

pH : No data available.

Melting point/range : No data available.

Boiling point/range : 421 °F (216 °C)

Flash point : 220 °F (104.5 °C) Pensky-Martens Closed Cup

Evaporation rate : No data available.

Flammability (solid, gas) : Refer to product classification in Section 2

Upper/lower

explosion/flammability limit

: No data available.

Vapor pressure : 0.06 mmHg

Water solubility : Miscible with water.

Relative vapor density : No data available.

Relative density : 1.15 (water = 1)

Partition coefficient: n-octanol/water [log Kow]

: No data available.

Auto-ignition temperature : No data available.

Decomposition temperature : No data available.

Viscosity : No data available.

: No data available.

Density : 71.792 lb/ft3 (1.15 g/cm3)

4/9

Versum Materials US,LLC

Version 1.0 Revision Date 02/20/2019 SDS Number 300000078629 Print Date 05/08/2019

10. STABILITY AND REACTIVITY

Chemical Stability : Stable under normal conditions.

Conditions to avoid : No data available.

Materials to avoid : Oxidizing agents.

Strong acids and strong bases.

Hazardous decomposition

products

: Carbon monoxide. Carbon dioxide (CO2).

Possibility of hazardous

Reactions/Reactivity

: No data available.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Likely routes of exposure

Effects on Eye : Causes eye irritation.

Effects on Skin : May cause skin irritation.

Inhalation Effects : No data available.

Ingestion Effects : No data available.

Symptoms : No data available.

Acute toxicity

Acute Oral Toxicity : No data is available on the product itself.

Acute Oral Toxicity - Components

Ethylene di(acetate) LD50 : > 5,000 mg/kg Species : Rat LD50 : > 5,000 mg/kg Species : Rat Species : Rat LD50 : > 5,000 mg/kg Species : Rat Sp

Inhalation : No data is available on the product itself.

Acute Dermal Toxicity : No data is available on the product itself.

Acute Dermal Toxicity - Components

 $\begin{array}{lll} \mbox{Ethylene di(acetate)} & \mbox{LD50 : > 2,000 mg/kg} & \mbox{Species : Rabbit} \\ \mbox{Propylene carbonate} & \mbox{LD50 : > 2,000 mg/kg} & \mbox{Species : Rabbit} \\ \end{array}$

Skin corrosion/irritation : May cause skin irritation.

Serious eye damage/eye : Irritating to eyes.

irritation

5/9

Versum Materials US,LLC

Version 1.0 Revision Date 02/20/2019 SDS Number 300000078629 Print Date 05/08/2019

Sensitization. : No data available.

Chronic toxicity or effects from long term exposures

Carcinogenicity : No data available.

Reproductive toxicity : No data is available on the product itself.

Germ cell mutagenicity : No data is available on the product itself.

Specific target organ systemic toxicity (single exposure)

: No data available.

Specific target organ systemic toxicity (repeated exposure)

: No data available.

Aspiration hazard : No data available.

Delayed and Immediate Effects and Chronic Effects from Short and Long Term Exposure

This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater.Repeated and/or prolonged exposures may result in:, Adverse skin effects (such as defatting, rash or irritation), Eye disease.

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Aquatic toxicity : No data is available on the product itself.

Toxicity to fish - Components

Ethylene di(acetate) LC50 (96 h): 40.45 mg/l Species: Fathead

minnow (Pimephales

promelas).

Propylene carbonate LC50 (96 h) : > 1,000 mg/l Species : Carp

(Cyprinus carpio).

Toxicity to daphnia - Components

Ethylene di(acetate) EC 50 (48 h) : > 116.3 mg/l Species : Daphnia Propylene carbonate EC 50 (48 h) : > 1,000 mg/l Species : Daphnia

Toxicity to other organisms : No data available.

Persistence and degradability

6/9

Versum Materials US,LLC Dynasolve M-35

Version 1.0 Revision Date 02/20/2019 SDS Number 300000078629 Print Date 05/08/2019

Biodegradability : The product is expected to be biodegradable.

Mobility : No data available.

Bioaccumulation : No data is available on the product itself.

Bioaccumulation - Components

Ethylene di(acetate) Potential to bioaccumulate is low. Propylene carbonate Negligible bioaccumulation potential.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused

products

: Contact supplier if guidance is required.

Contaminated packaging : Dispose of container and unused contents in accordance with federal, state,

and local requirements.

14. TRANSPORT INFORMATION

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

TDG

Not dangerous goods

Further Information

Not classified as dangerous in the meaning of transport regulations. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact customer service.

7/9

Versum Materials US,LLC

15. REGULATORY INFORMATION

Toxic Substance Control Act (TSCA) 12(b) Component(s):

None.

Country	Regulatory list	Notification	
USA	TSCA	Included on Inventory.	
EU	EINECS	Included on EINECS inventory or polymer	
		substance, monomers included on	
		EINECS inventory or no longer polymer.	
Canada	DSL	Included on Inventory.	
Australia	AICS	Included on Inventory.	
Japan	ENCS	Included on Inventory.	
South Korea	ECL	Included on Inventory.	
China	SEPA	Included on Inventory.	
Philippines	PICCS	Included on Inventory.	

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification Acute Health Hazard

EPA SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level None.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

16. OTHER INFORMATION

HMIS Rating

Health : 2 Flammability : 1 Physical hazard : 0

Prepared by : Versum Materials, Product Regulatory Department

Telephone : 800 837 2724

Preparation Date : 05/08/2019

For additional information, please visit Versum Materials' Product Stewardship web site.

http://www.versummaterials.com/productstewardship/

8/9

Versum Materials US,LLC

Version 1.0 Revision Date 02/20/2019

SDS Number 300000078629 Print Date 05/08/2019

Versum Materials US,LLC

Dynasolve M-35





1-800-375-0605 Option 8 for 24/7 Service

9/9



6550 Oley Speaks Way Canal Winchester, OH 43110



www.RudolphBros.Com RBCsupport@RudBro.Com