

# **EMPLOYEE OWNED SINCE 2023**

1-800-375-0605 | rbcsupport@rudbro.com | www.rudolphbros.com



Revision Number: 003.5 Issue date: 06/16/2022

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE EA 934NA AERO PART A

2.5OZ

Product type/use: Adhesive for the Aerospace Industry

Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

**IDH number:** 936934

Item number: AA9174301
Region: United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

WARNING: HARMFUL IF SWALLOWED.

CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

SUSPECTED OF CAUSING GENETIC DEFECTS.

| HAZARD CLASS           | HAZARD CATEGORY |
|------------------------|-----------------|
| ACUTE TOXICITY ORAL    | 4               |
| SKIN IRRITATION        | 2               |
| EYE IRRITATION         | 2A              |
| SKIN SENSITIZATION     | 1               |
| GERM CELL MUTAGENICITY | 2               |

# PICTOGRAM(S)





#### **Precautionary Statements**

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face

protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of

water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical

attention. Take off contaminated clothing.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)                           | CAS Number  | Percentage* |
|--|-------------|-------------|
| Triglycidyl-p-aminophenol                        | 5026-74-4   | 30 - 40     |
| Aluminum   | 7429-90-5   | 30 - 40     |
| Phenol polymer with formaldehyde, glycidyl ether | 28064-14-4  | 20 - 30     |
| Glass, oxide, chemicals                          | 65997-17-3  | 5 - 10      |
| Silica, amorphous, fumed, crystal-free           | 112945-52-5 | 1 - 5       |
| Treated fumed silica                             | 67762-90-7  | 1 - 5       |

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

# 4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately wash skin

thoroughly with soap and water. If symptoms develop and persist, get medical

attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

**Ingestion:** Get immediate medical attention. Do not induce vomiting. Never give anything

by mouth to a victim who is unconscious or is having convulsions.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically and supportively.

# 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Scrape up spilled material and place in a closed container for disposal.

Dispose of according to Federal, State and local governmental regulations.

IDH number: 936934

# 7. HANDLING AND STORAGE

**Handling:** For the Part A plus Part B adhesive mixture, follow curing schedule as

recommended in product literature. Do not heat Part A at temperatures greater than 80 °C (176 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full.

Storage: For safe storage, store between 0 °C (32°F) and 5 °C (41°F)

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Refrigerated storage is recommended to maintain

product quality.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                           | ACGIH TLV   | OSHA PEL   | AIHA WEEL | OTHER |
|--|---|--|-----------|-------|
| Triglycidyl-p-aminophenol                        | None  | None   | None      | None  |
| Aluminum   | 1 mg/m3 TWA<br>Respirable fraction.   | 15 mg/m3 PEL (as Al) Total dust. 5 mg/m3 PEL (as Al) Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. | None      | None  |
| Phenol polymer with formaldehyde, glycidyl ether | None  | None   | None      | None  |
| Glass, oxide, chemicals                          | 10 mg/m3 TWA<br>Inhalable dust.<br>3 mg/m3 TWA<br>Respirable fraction.  | 15 mg/m3 TWA Total<br>dust.<br>5 mg/m3 TWA<br>Respirable fraction.   | None      | None  |
| Silica, amorphous, fumed, crystal-free           | 10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. | 20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.  | None      | None  |
| Treated fumed silica                             | 10 mg/m3 TWA<br>Inhalable dust.<br>3 mg/m3 TWA<br>Respirable fraction.  | 15 mg/m3 TWA Total<br>dust.<br>5 mg/m3 TWA<br>Respirable fraction.   | None      | None  |

Engineering controls: Work should be done in an adequately ventilated area (i.e., ventilation

sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general

ventilation is not sufficient to control airborne contamination.

Respiratory protection: When dusts or thermal processing fumes are generated and ventilation is not

sufficient to effectively remove them, appropriate NIOSH/MSHA approved

respiratory protection must be provided.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid Color: Gray Odor: Slight Odor threshold: Not available. pH: Neutral . Vapor pressure: Not applicable Boiling point/range: Not determined Melting point/ range: Not determined

Specific gravity: 1.55 Vapor density: > 1

Flash point:

> 93 °C (> 199.4 °F)

Flammable/Explosive limits - lower:

Not determined

Not determined

Autoignition temperature:

Flammability:

Evaporation rate:

Not determined

Not flammable.

Not determined

Solubility in water: Slight

Partition coefficient (n-octanol/water): Not determined

VOC content: < 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)

Viscosity:Not available.Decomposition temperature:Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: May occur.

Hazardous decomposition

products:

IDH number: 936934

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Oxides of nitrogen.

**Incompatible materials:** Keep away from strong oxidizing agents, strong Lewis or mineral acids.

Reactivity: Not available.

Conditions to avoid: Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Do

not heat mixed adhesive unless curing surfaces to be bonded. Failure to observe these

precautions may result in excessive heat build-up causing an exotherm.

#### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### **Potential Health Effects/Symptoms**

**Inhalation:** May cause respiratory tract irritation.

Skin contact: This product may cause irritation to the skin. This product may cause an allergic skin reaction.

**Eye contact:** This product may cause irritation to the eyes.

**Ingestion:** Not a relevant route of exposure. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

| Hazardous Component(s)                           | LD50s and LC50s  | Immediate and Delayed Health Effects   |
|--|--|--|
| Triglycidyl-p-aminophenol                        | None   | Allergen, Irritant, Mutagen            |
| Aluminum   | Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 2.3 mg/l | Central nervous system, Irritant, Lung |
| Phenol polymer with formaldehyde, glycidyl ether | None   | Allergen, Irritant                     |
| Glass, oxide, chemicals                          | None   | Allergen, Respiratory                  |
| Silica, amorphous, fumed, crystal-free           | None   | Nuisance dust                          |
| Treated fumed silica                             | None   | Irritant                               |

| Hazardous Component(s)                           | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen<br>(Specifically Regulated) |
|--|----------------|-----------------|---|
| Triglycidyl-p-aminophenol                        | No             | No              | No  |
| Aluminum   | No             | No              | No  |
| Phenol polymer with formaldehyde, glycidyl ether | No             | No              | No  |
| Glass, oxide, chemicals                          | No             | No              | No  |
| Silica, amorphous, fumed, crystal-free           | No             | No              | No  |
| Treated fumed silica                             | No             | No              | No  |

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

International Air Transportation (ICAO/IATA)

**Proper shipping name:** Environmentally hazardous substance, solid, n.o.s. (Triglycidyl-p-aminophenol,

Bisphenol-F Epichlorhydrin resin)

Hazard class or division: 9
Identification number: UN 3077
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Triglycidyl-p-

aminophenol, Bisphenol-F Epichlorhydrin resin)

Hazard class or division: 9
Identification number: UN 3077
Packing group: III

Marine pollutant:Triglycidyl-p-aminophenol, Bisphenol-F Epichlorhydrin resinExceptions:Classified per IMDG Amendment 34; Effective Jan 1, 2010.

# 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: Triglycidyl-p-aminophenol (CAS# 5026-74-4).

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: Immediate Health, Delayed Health
This product contains the following

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Aluminum (CAS# 7429-90-5).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 8,11,12

Prepared by: Regulatory Affairs

Issue date: 06/16/2022

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.