





6550 Oley Speaks Way Canal Winchester, OH 43110

www.rudolphbros.com rbcsupport@rudbro.com

WACKER

Safety Data Sheet

Material: 60031637

Version: 2.2 (US)

WACKER SilGel® 612 B

Date of print: 06/18/2018

Date of last alteration: 06/16/2018

1. Product and company identification

1.1 Identification of the substance or preparation: WACKER SilGel® 612 B **Commercial product name:** Use of substance / preparation Industrial. Potting compound 1.2 Company/undertaking identification: Manufacturer/distributor: Wacker Chemie AG Hanns-Seidel-Platz 4 81737 München Germany Customer information: Wacker Chemical Corporation 3301 Sutton Road Adrian, Michigan 49221-9397 USA InfoLine: Tel (517) 264-8240, Fax (517) 264-8740 Hours of operation: Monday - Friday, 8 am to 5 pm (eastern standard time) Corporate website: www.wacker.com Emergency telephone no. (24h): (517) 264-8500 (800) 424-9300 (CHEMTREC, USA) Transportation emergency: (703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

2.	Hazards identification
2.1	Classification of the substance or mixture
	Classification (GHS):
	Not a hazardous substance or mixture.
2.2	Label elements
	Labelling (GHS):
	No labeling according to GHS required.
2.3	Other hazards
I	No data available.
3.	Composition/information on ingredients

3.1 Chemical characterization (preparation)

Chemical characteristics

Polydimethylsiloxane with functional groups and auxiliaries for addition cross-linking

3.2 Information on ingredients:

This material does not contain any ingredients above the permitted limit(s).

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

Material: 60031637

WACKER

WACKER SilGel® 612 B

Date of last alteration: 06/16/2018

Version: 2.2 (US)

Date of print: 06/18/2018

4. First-aid measures

4.1 General information:

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

4.2 After inhalation

Material cannot be inhaled under normal conditions. No special treatment required.

4.3 After contact with the skin

After skin contact wipe off excess material with cloth or paper. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

4.4 After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

4.5 After swallowing

No special measures are required after swallowing.

5. Fire-fighting measures

5.1 Flammable properties:

Property:	Value:	Method:
Flash point	> 200 °C (> 392 °F)	(DIN 51376)
Boiling point / boiling range:	not applicable	
Lower explosion limit (LEL):	not applicable	
Upper explosion limit (UEL):	not applicable	
Ignition temperature:	> 450 °C (> 842 °F)	(DIN 51794)
NFPA Hazard Class (comb./flam.liquid):	IIIB	

5.2 Fire and explosion hazards:

This material does not present any unusual fire or explosion hazards.

5.3 Recommended extinguishing media:

water-mist , carbon dioxide , sand , dry chemical or alcohol-resistant foam .

5.4 Unsuitable extinguishing media:

water-spray , sharp water jet .

5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide and incompletely burnt hydrocarbons .

5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water.

6. Accidental release measures

6.1 Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

HAZWOPER PPE Level: D

6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

WACKER

Safety Data Sheet

Material: 60031637	WACKER SilGel® 612 B	
Version: 2.2 (US)	Date of print: 06/18/2018	Date of last alteration: 06/16/2018

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

6.3 Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

7. Handling and storage

7.1 Handling

Precautions for safe handling:

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

Precautions against fire and explosion:

Observe the general rules for fire prevention.

7.2 Storage

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place.

8. Exposure controls and personal protection

8.1 Engineering controls

Ventilation:

Use with adequate ventilation.

Local exhaust:

not necessary

8.2 Associate substances with specific control parameters such as limit values

Maximum airborne concentrations at the workplace:

CAS No. Material	Туре	mg/m ³	ppm	Dust fract.
------------------	------	-------------------	-----	-------------

none known

8.3 Personal protection equipment (PPE)

Respiratory protection: Respiratory protection is not normally required.

Hand protection:

Recommendation: Any liquid-tight rubber or vinyl gloves.

Eye protection:

Recommendation: Safety glasses with side shields.

Other protective clothing or equipment:

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

8.4 General hygiene and protection measures:

When handling do not eat, drink, smoke or apply cosmetics. Wash thoroughly after handling.

Material: 60031637

WACKER

WACKER SilGel® 612 B

Version: 2.2 (US)

Date of print: 06/18/2018

Date of last alteration: 06/16/2018

9. Physical and chemical properties

9.1 Appearance

9.2

9.3

Physical state / form		
Odour		
Safety parameters		
Property:	Value:	Method:
Melting point / melting range		
Boiling point / boiling range	not applicable	
Flash point	> 200 °C (> 392 °F)	(DIN 51376)
Ignition temperature	> 450 °C (> 842 °F)	(DIN 51794)
Lower explosion limit (LEL)		
Upper explosion limit (UEL)	not applicable	
Vapour pressure		
Density	: 1.00 g/cm³ at 20 °C (68 °F)	(DIN 51757)
Water solubility / miscibility	: virtually insoluble at 20 °C (68 °F)	
pH-Value	not applicable	
Viscosity (dynamic)	approx. 1000 mPa.s at 23 °C (73 °F)	
Further information		
Odour limit:	no data available	
Thermal decomposition:	> 200 °C (> 392 °F)	

10. Stability and reactivity

10.1 General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

none known

10.3 Materials to avoid

none known

10.4 Hazardous decomposition products

If stored and handled properly: none known . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

10.5 Further information:

Hazardous polymerization cannot occur.

11. Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Product details:

Route of exp	osure Result/Effect	Species/Test system	Source
oral	LD ₅₀ : > 5000 mg/kg	rat	Conclusion by analogy
dermal	LD ₅₀ : > 2008 mg/kg	rat	Conclusion by analogy

11.1.2 Skin corrosion/irritation

WACKER

WACKER SilGel® 612 B

Date of last alteration: 06/16/2018

Version: 2.2 (US)

Date of print: 06/18/2018

Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by
		analogy

11.1.3 Serious eye damage / eye irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by
-		analogy

11.1.4 Respiratory or skin sensitization

Product details:

Route of exposure	Result/Effect	Species/Test system	Source
dermal	not sensitizing	guinea-pig; Bühler	Conclusion by
			analogy
			OECD 406

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.11 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

12. Ecological information

12.1 Toxicity

Assessment:

Based on available data no effects on aquatic organisms that are relevant for classification must be expected for the product up to its limits of water solubility. According to current knowledge adverse effects on water purification plants are not expected.

WACKER

Safety Data Sheet

Material: 60031637

WACKER SilGel® 612 B

Date of last alteration: 06/16/2018

Version: 2.2 (US)

Date of print: 06/18/2018

Product details:

Result/Effect	Species/Test system	Source
> 1000 mg/l (nominal)	static (water-accommodated fraction)	literature
effect level > maximum achievable concentration	Fish (96 h)	(Polydimethylsiloxan e)
EC ₅₀ : > 0.0001 mg/l (measured)	static (water-accommodated fraction)	literature
effect level > maximum achievable concentration	Daphnia magna (48 h)	(Polydimethylsiloxan e)
IC ₅₀ (growth rate): > 100000 mg/l (nominal)	static (water-accommodated fraction)	literature
	Marine alga (skeleonema costatum) (72 h)	(Polydimethylsiloxan e)
NOEC: > 10000 mg/kg	feeding study	literature
	rainbow trout (Oncorhynchus mykiss) (28 d)	(Polydimethylsiloxan e)
NOEC (mortality, growth, reproduction): > 500 mg/kg	exposure via sediment	literature
The exposure to treated sediment did not result in	Daphnia magna (21 d)	(Polydimethylsiloxan
effects.		e)

12.2 Persistence and degradability

Assessment:

Silicone content: biologically not degradable. Elimination by adsorption to activated sludge.

12.3 Bioaccumulative potential

Assessment:

Bioaccumulation is not expected to occur.

12.4 Mobility in soil

Assessment:

Polymer component: insoluble in water. Adsorbs on soil.

12.5 Other adverse effects

none known

13. Disposal considerations

13.1 Product disposal

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.2 Packaging disposal

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

14. Transport information

14.1 US DOT & CANADA TDG SURFACE

Valuation Not regulated for transport

14.2 Transport by sea IMDG-Code

Valuation Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation Not regulated for transport

Material: 60031637

WACKER

Version: 2.2 (US)

WACKER SilGel® 612 B

Date of print: 06/18/2018

Date of last alteration: 06/16/2018

15. Regulatory information

15.1 U.S. Federal regulations

TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazard Class:

This product does not present any SARA 311/312 hazards.

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

HAPS (Hazardous Air Pollutants):

CAS No.	Chemical	Upper limit wt. %
108-88-3	Toluene	<=0.0060

15.2 U.S. State regulations

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This material does not contain any chemicals known to the State of California to cause cancer.

California Proposition 65 Reproductive Toxins:

108-88-3 Toluene

Massachusetts Substance List: This material contains no listed components.

New Jersey Right-to-Know Hazardous Substance List:

This material contains no listed components.

Pennsylvania Right-to-Know Hazardous Substance List: This material contains no listed components.

15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

South Korea (Republic of Korea):	
Japan:	This product is listed in, or complies with, the substance inventory. ENCS (Handbook of Existing and New Chemical Substances): This product is listed in an approximate with the substances inventory.
New Zealand:	This product is listed in, or complies with, the substance inventory. NZIOC (New Zealand Inventory of Chemicals):
	This product is listed in, or complies with, the substance inventory. (For a correct
	interpretation of the New Zealand status, additional information like GHS classification or Group Standard is required.)
Australia:	AICS (Australian Inventory of Chemical Substances):
People's Republic of China:	This product is listed in, or complies with, the substance inventory. IECSC (Inventory of Existing Chemical Substances in China):
	This product is listed in, or complies with, the substance inventory.
Canada:	DSL (Domestic Substance List): This product is listed in, or complies with, the substance inventory.
Philippines:	PICCS (Philippine Inventory of Chemicals and Chemical Substances):
United States of America (USA):	This product is listed in, or complies with, the substance inventory. TSCA (Toxic Substance Control Act Chemical Substance Inventory):
	All components of this product are listed as active or are in compliance with the substance inventory.

WACKER

Safety Data Sheet

Material: 60031637	WACKER SilGel® 612 B	
Version: 2.2 (US)	Date of print: 06/18/2018	Date of last alteration: 06/16/2018
Taiwan (Republic of China)	The Taiwanese chemicals regulation re or TCSI-compliant substances if import exceed the trigger quantity of 100 kg/a	th, the substance inventory. General note: equires a phase 1 registration for TCSI-listed is to Taiwan or manufacturing in Taiwan
European Economic Area (EEA	manufactured within the EEA by the su	ns for substances imported into the EEA or pplier mentioned in section 1 are fulfilled by ations for substances imported into the EEA

16. Other information

16.1 Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

All deliveries are subject to the WACKER SILICONES Health Care Policy, which is available at www.wacker.com.

16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial	ppm - Parts per Million
Hygienists	SARA - Superfund Amendments and Reauthorization Act
DOT - Department of Transportation	STEL - Short Term Exposure Limit
hPa - Hectopascals	TSCA - Toxic Substances Control Act
mPa*s - Milli Pascal-Seconds	TWA - Time Weighted Average
OSHA - Occupational Safety and Health Administration	WHMIS - Canadian Workplace Hazardous Materials
PEL - Permissible Exposure Limit	Identification System
Flash point determination methods	Tagliabue (Tag) closed cup Cleveland open cup Pensky-Martens closed cup Setaflash or Rapid closed cup

16.3 Conversion table:

Pressure:	1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa
Viscosity:	1 mPa*s = 1 centipoise (cP)







6550 Oley Speaks Way Canal Winchester, OH 43110

www.rudolphbros.com rbcsupport@rudbro.com