



Safety Data Sheet

24 Hour Emergency Phone Numbers
Medical/Poison Control:
In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

Transportation/National Response Center:

1-800-535-5053
1-352-323-3500

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

1. Identification

Product Name:	DYNAGRIP Advanced Subfloor Construction Adhesive	Revision Date:	4/12/2022
Product UPC Number:	070798270428, 070798275164	Supersedes Date:	12/29/2021
Manufacturer:	DAP Global Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)	Product Use/Class:	Construction Adhesive
	SDS Coordinator: MSDS@dap.com	SDS No:	7008301
	Emergency Telephone: Transportation: 1-800-535 -5053 1-352-323-3500 Poison Control: 1-800-222-1222	Preparer:	Regulatory and Environmental Affairs

2. Hazards Identification

EMERGENCY OVERVIEW: DANGER! Extremely flammable liquid and vapor. Vapors may cause flash fire or explosion. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Flammable liquid and vapor. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Keep container closed and away from heat, sparks, and open flame. Store away from caustics and oxidizers. Avoid breathing vapor. Use only with adequate ventilation. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Irritating to eyes, respiratory system and skin. Harmful or fatal if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage. Aspiration may cause pulmonary edema and pneumonitis. May affect the brain or nervous system causing dizziness, headache or nausea.

GHS Classification

Eye Irrit. 2, Flam. Liq. 1, STOT SE 3 NE

Symbol(s) of Product**Signal Word**

Danger

Possible Hazards

68% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Flammable Liquid, category 1	H224	Extremely flammable liquid and vapour.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.

GHS LABEL PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use... to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container.

GHS SDS PRECAUTIONARY STATEMENTS

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Acetone	67-64-1	10-30	GHS02-GHS07	H225-319-336
Clay	1332-58-7	5-10	No Information	No Information
Petroleum hydrocarbon resin	64742-16-1	3-7	No Information	No Information
Methyl acetate	79-20-9	1-5	GHS02-GHS07	H225-319-336
Magnesite	546-93-0	1-5	No Information	No Information
Toluene	108-88-3	1-5	GHS02-GHS07-GHS08	H225-304-315-332-335-336-373
Hydrous aluminum silicate	8031-18-3	1-5	GHS07	H319-332-335
Diethylene glycol dibenzoate	120-55-8	1-5	GHS07	H312

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. NOTE: Only trained personnel should administer artificial respiration or give oxygen.

FIRST AID - SKIN CONTACT: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist. Remove and wash contaminated clothing. DO NOT try to peel the solidified material from the skin or use solvents or thinners to dissolve it. The use of vegetable oil or mineral oil is recommended for removal of this material from the skin. Flush exposed area with water while removing contaminated clothing. Get medical attention if irritation persists. To remove from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Eliminate sources of ignition: heat, electrical equipment, sparks and flames. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Vapors may form explosive mixtures with air. Containers may explode if exposed to extreme heat. Empty containers retain product residue (liquid and/or vapor). Vapor can ignite potentially causing an explosion.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Remove all sources of ignition. Keep away from open flames, hot surfaces and sources of ignition. Provide adequate ventilation. Avoid heat, sparks and open flames. Wear appropriate personal protection. Avoid breathing vapor and contact with eyes, skin and clothing. Use in well ventilated area. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions. Empty containers retain product residue (liquid and/or vapor). Vapor can ignite potentially causing an explosion. Do not use in areas where static sparks may be generated. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. Construction and repair activities can adversely affect indoor air quality. Consult with occupants or a representative (i.e. maintenance, building manager, industrial hygienist, or safety officer) to determine ways to minimize impact.

STORAGE: Store away from sources of ignition and heat. Do not store at temperatures above 120 °F (49 °C). Store containers away from excessive heat and freezing. Store away from caustics and oxidizers. Keep containers tightly closed.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Acetone	250 ppm TWA	500 ppm STEL	1000 ppm TWA, 2400 mg/m ³ TWA	N.E.
Clay	2 mg/m ³ TWA particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	N.E.	15 mg/m ³ TWA total dust, 5 mg/m ³ TWA respirable fraction	N.E.
Petroleum hydrocarbon resin	N.E.	N.E.	N.E.	N.E.
Methyl acetate	200 ppm TWA	250 ppm STEL	200 ppm TWA, 610 mg/m ³ TWA	N.E.
Magnesite	N.E.	N.E.	N.E.	N.E.
Toluene	20 ppm TWA	N.E.	200 ppm TWA	300 ppm Ceiling
Hydrous aluminum silicate	N.E.	N.E.	N.E.	N.E.
Diethylene glycol dibenzoate	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. In case of insufficient ventilation, wear suitable respiratory equipment. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



SKIN PROTECTION: Solvent-resistant gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Provide eyewash and solvent impervious apron if body contact may occur.



HYGIENIC PRACTICES: Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

Appearance:	Tan	Physical State:	Paste
Odor:	Strong Solvent	Odor Threshold:	Not Established
Density, g/cm ³ :	1.37 - 1.37	pH:	Not Applicable
Freeze Point, °C:	Not Established	Viscosity (mPa.s):	Not Established
Solubility in Water:	Not Established	Partition Coeff., n-octanol/water:	Not Established
Decomposition Temperature, °C:	Not Established	Explosive Limits, %:	N.E. - N.E.
Boiling Range, °C:	N.A. - N.A.	Auto-Ignition Temperature, °C	Not Established
Minimum Flash Point, °C:	-17	Vapor Pressure, mmHg:	Not Established
Evaporation Rate:	Not Established	Flash Method:	Pensky-Martens Closed Cup
Vapor Density:	Not Established	Flammability, NFPA:	Flammable Liquid Class IA
Combustible Dust:	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing. Keep away from open flames, hot surfaces and sources of ignition. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Avoid contact with skin, eyes and clothing. Do not smoke.

INCOMPATIBILITY: Open flames, hot surfaces and sources of ignition. Keep away from strong oxidizing agents, heat and open flames. Exothermic reaction with strong acids. Incompatible with strong bases and oxidizing agents. Avoid contact with strong acids and oxidizable organic materials in the presence of heat.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., CO_x, NO_x.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation of vapors may cause irritation of the nose, throat, lungs and respiratory tract. Inhalation of vapors in high concentration may cause shortness of breath (lung edema). Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Prolonged, repeated or high exposures may cause central nervous system depression leading to headaches, nausea, drowsiness, dizziness, and possibly narcosis. In extreme cases, may cause loss of consciousness.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

EFFECT OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation. Signs and symptoms may include: pain, tears, swelling, redness and blurred vision.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful or fatal if swallowed. May cause gastrointestinal disturbances with dizziness and central nervous system depression. If ingested, may cause depressed respiration. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis, which can be fatal.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause skin, respiratory, kidney and liver damage. May cause kidney and liver damage as well as developmental and reproductive toxicity. Prolonged or repeated inhalation of solvent vapors may cause irregular heartbeat. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability and loss of coordination. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Overexposure or misuse of toluene can cause liver, kidney, and brain damage as well as cardiac abnormalities. There have been cases of aplastic anemia from toluene in industrial exposures (ACGIH, 1992). Increased coagulation time and reduced clotting factors have also been found, which are indicators of damage to the bone marrow (Clayton & Clayton, 1994). Symptoms include: loss of memory, loss of intellectual ability and loss of coordination. Constituents of this product include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Skin Absorption, Inhalation

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
67-64-1	Acetone	5250 mg/kg mouse	>15688 mg/kg rabbit	50 mg/L Rat
1332-58-7	Clay	>5000 mg/kg Rat	>5000 mg/kg Rat	N.I.
64742-16-1	Petroleum hydrocarbon resin	N.I.	N.I.	N.I.
79-20-9	Methyl acetate	>6482 mg/kg Rat	>5000 mg/kg Rabbit	49.2 mg/L Rabbit
546-93-0	Magnesite	>2000 mg/kg Rat	N.I.	N.I.
108-88-3	Toluene	2600 mg/kg Rat	12000 mg/kg Rabbit	12.5 mg/L Rat
8031-18-3	Hydrous aluminum silicate	N.I.	N.I.	N.I.
120-55-8	Diethylene glycol dibenzoate	2830 mg/kg Rat	2000 mg/kg Rabbit	>200 mg/L Rat

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: Residues and spilled material are hazardous waste due to ignitability. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from

Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Do not flush into surface water or sanitary sewer system. Do not empty into drains. Do not re-use empty containers. The container for this product can present explosion or fire hazards, even when emptied. To avoid risk of injury, do not cut, puncture, or weld on or near this container.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers.

14. Transport Information

DOT UN/NA Number: UN1133
DOT Proper Shipping Name: Adhesives, containing a flammable liquid
DOT Technical Name: N.A.
DOT Hazard Class: 3 Flammable liquid
Hazard SubClass: N.A.
Packing Group: III

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Toluene	108-88-3

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

16. Other Information

Revision Date: 4/11/2022 **Supersedes Date:** 12/29/2021

Reason for revision: Substance and/or Product Properties Changed in Section(s):
01 - Product Information
08 - Exposure Controls/Personal Protection

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	Flammability:	Reactivity:	Personal Protection:
2*	4	1	X

VOC Less Water Less Exempt Solvent, g/L: 50.8

VOC Material, g/L: 30

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 2.13

VOC Actual, Wt/Wt%: 2.2

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.