

PLOYEE OWNED SINCE 20

1-800-375-0605 | rbcsupport@rudbro.com | www.rudolphbros.co



Revision Number: 004.1

PRODUCT AND COMPANY IDENTIFICATION 1.

Product name:

Product type/use: Restriction of Use: Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE EA 9394 AERO PART B GAL known as EA 9394 PART B GALLON 2-Component epoxy adhesive None identified

IDH number:


937063

AB9277018 Item number: **Region: United States** Contact information: Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

HAZARDS IDENTIFICATION 2.

EMERGENCY OVERVIEW DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1C - Corrosive
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1



Precautionary Statements

Prevention:	Do not breathe dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.
Response:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Tetraethylene pentamine	112-57-2	30 - 60	
N,N'-Bis(3-aminopropyl)piperazine	7209-38-3	30 - 60	
Silica, amorphous, fumed, crystfree	112945-52-5	5 - 10	
3,6,9,12- tetraazatetradecamethylenediamine	4067-16-7	5 - 10	
IDH number: 937063	Product name: LOCTITE EA 9394 AERO PART B GAL known as EA 9394 PART B GALLON		

IDH number: 937063

9394 AERO PART B GAL known as EA 9394 PART B GALLON Product nar Page 1 of 6

3,6-diazaoctanethylenediamine	112-24-3	1 - 5
Carbon black	1333-86-4	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4.	FIRST AID MEASURES
Inhalation:	If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medica attention.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get immediate medical attention. Do not induce vomiting. Never give anythin by mouth to a victim who is unconscious or is having convulsions.
Symptoms:	See Section 11.
Notes to physician:	Treat symptomatically and supportively.
5. F	IRE FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
6. ACCII	DENTAL RELEASE MEASURES
personal protection recommended in Section of the s	on 8, isolate the hazard area and deny entry to unnecessary and
Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.
7.	ANDLING AND STORAGE
Handling:	For the Part A plus Part B adhesive mixture, follow curing schedule as recommended in product literature. Do not heat Part B at temperatures great than 100 °C (212 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. Do not cut

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from

grind, weld, or drill on or near this container.

incompatible materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Tetraethylene pentamine	None	None	1 ppm (5 mg/m3) TWA Aerosol. (SKIN) Aerosol. (Skin sensitizer.)	None
N,N'-Bis(3-aminopropyl)piperazine	None	None	None	None
Silica, amorphous, fumed, crystfree	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
3,6,9,12- tetraazatetradecamethylenediamine	None	None	None	None
3,6-diazaoctanethylenediamine	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Carbon black	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None

Engineering controls:

Respiratory protection:

Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.

Eye/face protection:

Skin protection:

Safety goggles or safety glasses with side shields.

Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Brown
Odor:	Amine
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	< 0.1 mm hg
Boiling point/range:	340 °C (644°F)
Melting point/ range:	Not determined
Specific gravity:	1.0
Vapor density:	8.6
Flash point:	> 93 °C (> 199.4 °F)
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Autoignition temperature:	Not determined
Flammability:	Not applicable
Evaporation rate:	Not determined
Solubility in water:	Complete
Partition coefficient (n-octanol/water):	Not determined
VOC content:	< 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)
Viscosity:	Not available.
Decomposition temperature:	> 200 °C

Product name: LOCTITE EA 9394 AERO PART B GAL known as EA 9394 PART B GALLON Page 3 of 6

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	May occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
Incompatible materials:	Keep away from strong oxidizing agents, strong Lewis or mineral acids.
Reactivity:	Not available.
Conditions to avoid:	Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Do not heat mixed adhesive unless curing surfaces to be bonded. Failure to observe these precautions may result in excessive heat build-up causing an exotherm. The exotherm has the potential for release of toxic gasses.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Can cause severe irritation and burns to the respiratory tract.
Skin contact:	This product is severely irritating to the skin and may cause burns. Repeated or prolonged skin contact may result in allergic sensitization. This product may be harmful if it is absorbed
	through the skin.
Eye contact:	This product is severely irritating to the eyes and may cause eye burns.
Ingestion:	Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Tetraethylene pentamine	Oral LD50 (Rat) = 3.99 g/kg Oral LD50 (Rat) = 2.1 g/kg Dermal LD50 (Rabbit) = 0.66 g/kg	Irritant, Mutagen, Allergen	
N,N'-Bis(3-aminopropyl)piperazine	None	No Records	
Silica, amorphous, fumed, crystfree	None	No Data	
3,6,9,12- tetraazatetradecamethylenediamine	None	Irritant, Allergen	
3,6-diazaoctanethylenediamine	None	Allergen, Corrosive, Developmental, Irritant, Mutagen	
Carbon black	Oral LD50 (Rat) = > 8,000 mg/kg	Respiratory, Some evidence of carcinogenicity	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Tetraethylene pentamine	No	No	No
N,N'-Bis(3-aminopropyl)piperazine	No	No	No
Silica, amorphous, fumed, crystfree	No	No	No
3,6,9,12- tetraazatetradecamethylenediamine	No	No	No
3,6-diazaoctanethylenediamine	No	No	No
Carbon black	No	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information:

Do not empty into drains, soil or bodies of water.

13. DISPOSAL CONSIDERATIONS Information provided is for unused product only. Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations. 14. **TRANSPORT INFORMATION** The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration. U.S. Department of Transportation Ground (49 CFR) Proper shipping name: Amines, solid, corrosive, n.o.s. (Tetraethylene pentamine, Substituted piperazine) Hazard class or division: 8 Identification number: UN 3259 Packing group: ш International Air Transportation (ICAO/IATA) Proper shipping name: Amines, solid, corrosive, n.o.s. (Tetraethylene pentamine, Substituted piperazine) Hazard class or division: 8 Identification number: UN 3259 Packing group: ш Water Transportation (IMO/IMDG) Proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (Tetraethylene pentamine, Substituted piperazine) Hazard class or division: 8 Identification number: UN 3259 Packing group: Ш Marine pollutant: Tetraethylene pentamine 15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health None above reporting de minimis.
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.
ada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: minor updates 3, 11

Prepared by: Regulatory Affairs

Issue date:

Can

07/20/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.