

1-800-375-0605 | rbcsupport@rudbro.com | www.rudolphbros



**Revision Number: 004.1** Issue date: 07/20/2022

# 1. PRODUCT AND COMPANY IDENTIFICATION

IDH number: Product name: **LOCTITE EA 9394 AERO PART B** 937066

5GAL

AB9277019 Product type/use: 2-Component epoxy adhesive Item number: Region: **United States** 

Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW				
DANGER:	CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.			
	MAY CAUSE AN ALLERGIC SKIN REACTION			

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1C - Corrosive
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

#### PICTOGRAM(S)



#### **Precautionary Statements**

Prevention: Do not breathe dust or fumes. Wash affected area thoroughly after handling. Contaminated

work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye

and face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off Response:

immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash

contaminated clothing before reuse.

Store locked up. Storage:

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Tetraethylene pentamine	112-57-2	30 - 60
N,N'-Bis(3-aminopropyl)piperazine	7209-38-3	30 - 60
Silica, amorphous, fumed, crystfree	112945-52-5	5 - 10
3,6,9,12- tetraazatetradecamethylenediamine	4067-16-7	5 - 10

Product name: LOCTITE EA 9394 AERO PART B 5GAL IDH number: 937066

3,6-diazaoctanethylenediamine	112-24-3	1 - 5
Carbon black	1333-86-4	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

# 4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately wash skin

thoroughly with soap and water. If symptoms develop and persist, get medical

attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Get immediate medical attention. Do not induce vomiting. Never give anything

by mouth to a victim who is unconscious or is having convulsions.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically and supportively.

#### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray. Closed containers may

rupture (due to build up of pressure) when exposed to extreme heat.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Scrape up spilled material and place in a closed container for disposal.

Dispose of according to Federal, State and local governmental regulations.

# 7. HANDLING AND STORAGE

Handling: For the Part A plus Part B adhesive mixture, follow curing schedule as

recommended in product literature. Do not heat Part B at temperatures greater than 100 °C (212 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. Do not cut,

grind, weld, or drill on or near this container.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER	
Tetraethylene pentamine	None	None	1 ppm (5 mg/m3) TWA Aerosol. (SKIN) Aerosol. (Skin sensitizer.)	None	
N,N'-Bis(3-aminopropyl)piperazine	None	None	None	None	
Silica, amorphous, fumed, crystfree	3 mg/m3 TWA 50 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. 15 mg/m3 TWA Total dust. 15 MPPCF TWA	3 mg/m3 TWA 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. 15 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.		None	None
3,6,9,12- tetraazatetradecamethylenediamine	None	None	None	None	
3,6-diazaoctanethylenediamine	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None	
Carbon black	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None	

Engineering controls: Ventilation should effectively remove and prevent buildup of any dust

generated from the handling of this product.

**Respiratory protection:** When dusts or thermal processing fumes are generated and ventilation is not

sufficient to effectively remove them, appropriate NIOSH/MSHA approved

respiratory protection must be provided.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:PasteColor:BrownOdor:AmineOdor threshold:Not available.pH:Not applicableVapor pressure:< 0.1 mm hg</th>Boiling point/range:340 °C (644°F)Melting point/ range:Not determined

Specific gravity: 1.0 Vapor density: 8.6

> 93 °C (> 199.4 °F) Flash point: Not determined Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Not determined Autoignition temperature: Not determined Flammability: Not applicable **Evaporation rate:** Not determined Complete Solubility in water: Not determined Partition coefficient (n-octanol/water):

VOC content: < 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)

Viscosity: Not available.

Decomposition temperature: > 200 °C

IDH number: 937066 Product name: LOCTITE EA 9394 AERO PART B 5GAL

# 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: May occur.

**Hazardous decomposition** 

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Oxides of nitrogen.

Incompatible materials: Keep away from strong oxidizing agents, strong Lewis or mineral acids.

Reactivity: Not available.

Conditions to avoid: Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Do

not heat mixed adhesive unless curing surfaces to be bonded. Failure to observe these precautions may result in excessive heat build-up causing an exotherm. The exotherm has the

potential for release of toxic gasses.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### **Potential Health Effects/Symptoms**

**Inhalation:** Can cause severe irritation and burns to the respiratory tract.

Skin contact: This product is severely irritating to the skin and may cause burns. Repeated or prolonged skin

contact may result in allergic sensitization. This product may be harmful if it is absorbed

through the skin.

**Eye contact:** This product is severely irritating to the eyes and may cause eye burns.

Ingestion: Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the

digestive tract.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Tetraethylene pentamine	Oral LD50 (Rat) = 3.99 g/kg Oral LD50 (Rat) = 2.1 g/kg Dermal LD50 (Rabbit) = 0.66 g/kg	Irritant, Mutagen, Allergen
N,N'-Bis(3-aminopropyl)piperazine	None	No Records
Silica, amorphous, fumed, crystfree	None	No Data
3,6,9,12- tetraazatetradecamethylenediamine	None	Irritant, Allergen
3,6-diazaoctanethylenediamine	None	Allergen, Corrosive, Developmental, Irritant, Mutagen
Carbon black	Oral LD50 (Rat) = > 8,000 mg/kg	Respiratory, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Tetraethylene pentamine	No	No	No
N,N'-Bis(3-aminopropyl)piperazine	No	No	No
Silica, amorphous, fumed, crystfree	No	No	No
3,6,9,12- tetraazatetradecamethylenediamine	No	No	No
3,6-diazaoctanethylenediamine	No	No	No
Carbon black	No	Group 2B	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Do not empty into drains, soil or bodies of water.

IDH number: 937066 Product name: LOCTITE EA 9394 AERO PART B 5GAL

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, solid, corrosive, n.o.s. (Tetraethylene pentamine, Substituted piperazine)

Hazard class or division: 8

Identification number:UN 3259Packing group:III

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, solid, corrosive, n.o.s. (Tetraethylene pentamine, Substituted piperazine)

Hazard class or division: 8

Identification number: UN 3259
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (Tetraethylene pentamine, Substituted

piperazine)

Hazard class or division: 8

Identification number: UN 3259
Packing group: III

Marine pollutant: Tetraethylene pentamine

#### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

IDH number: 937066

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: minor updates 3, 11

Prepared by: Regulatory Affairs

Issue date: 07/20/2022

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 937066